


K 300 W

6,8 mm coaxial cable with copper conductor



K 300 W



K 300 W - K 300 W3

Technical specifications. 6,8 mm coaxial cable with copper conductor K 300 W



	K 300 W	K 300 W3
Code	0703420	0703422
Inner conductor (mm) Ø	1,13 Cu	1,13 Cu
Dielectric (mm) Ø	4,6 PE physical foam	4,6 PE physical foam
Foil material	Al / Pet / Al	Al / Pet / Al
Braiding material	Al	Al
Number of wires (braiding)	168	168
Braiding composition	24 x 7 x 0,12 mm	24 x 7 x 0,12 mm
Braiding coverage	95%	95%
Outer jacket (mm) Ø	6,8 PVC white	6,8 PVC white
Screening factor (30 - 900 MHz)	> 100 dB	> 100 dB
Nominal attenuation (dB / 100 m)		
	47 MHz	3,7
	175 MHz	6,7
	470 MHz	11,2
	862 MHz	16,2
	950 MHz	17,5
	1350 MHz	21,8
	1750 MHz	25,0
	2150 MHz	28,2
Lenght (m)	100	300
Impedance (Ω)	75	75
Net weight (Kg)	4,32	13,0
Presentation	100 m cardboard spool	300 m wooden drum
Packing quantity	1 / 4	1