

TAPS

 QuiCoax®

DQC 816 · DQC 820 · DQC 824

- ✓ QuiCoax connection system
- ✓ 8 Outputs
- ✓ Low insertion loss
- ✓ DC pass in trunk line

Ek

EKSELANS BY ITS



DQC 816

01



Reduce to minimum installation time

02



No need of tools

03



Guarantees an excellent connected and minimizes the space

04



Very high shielding factor CLASS A +10dB throughout the band

05



Eliminate the use of connectors and associated costs

06



QuiCoax, the new Standard of Connection



TECHNICAL TABLE

REFERENCE	DQC816	DQC820	DQC824
CODE			
LOSS			
Insertion loss (in-out) 5-47 MHz	<4.1 dB	<1.8 dB	<1.1 dB
Insertion loss (in-out) 47-950 MHz	<4.1 dB	<2.7 dB	<1.8 dB
Insertion loss (in-out) 950-2150 MHz	<4.2 dB	<3.6 dB	<2.5 dB
Insertion loss (in-out) 2150-2400 MHz	<4.4 dB	<3.9dB	<2.8 dB
Tap loss (in-tap) 5-47 MHz	16 dB ±1.5 dB	20 dB ±1.5 dB	24 dB ±1.5 dB
Tap loss (in-tap) 47-950 MHz	16 dB ±1.5 dB	20 dB ±1.5 dB	24 dB ±1.5 dB
Tap loss (in-tap) 950-2150 MHz	16 dB ±1.5 dB	20 dB ±1.5 dB	24 dB ±1.5 dB
Tap loss (in-tap) 2150-2400 MHz	16 dB ±1.5 dB	20 dB ±1.5 dB	24 dB ±1.5 dB
ISOLATION			
Isolation (tap-tap) 5-47 MHz	>30 dB	>28 dB	>30 dB
Isolation (tap-tap) 47-950 MHz	>31 dB	>33 dB	>35 dB
Isolation (tap-tap) 950-2150 MHz	>32 dB	>40 dB	>40 dB
Isolation (tap-tap) 2150-2400 MHz	>35 dB	>35 dB	>35 dB
Isolation (tap-out) 5-47 MHz	>32 dB	>20 dB	>33 dB
Isolation (tap-out) 47-950 MHz	>36 dB	>18 dB	>29 dB
Isolation (tap-out) 950-2150 MHz	>32 dB	>20 dB	>29 dB
Isolation (tap-out) 2150-2400 MHz	>35 dB	>21 dB	>28 dB
RETURN LOSS			
Return loss 5-47 MHz	>14 dB	>15 dB	>15 dB
Return loss 47-950 MHz	>14 dB	>15 dB	>15 dB
Return loss 950-2150 MHz	>15 dB	>15 dB	>15 dB
Return loss 2150-2400 MHz	>15 dB	>14 dB	>14 dB
OPERATIONAL			
Impedance	75 Ω		
Application	SAT, MATV 2.4Ghz +DC		
Screening Efficiency	EN50083-2 Class A +10dB		
DC Passthrough	Yes (max. 500mA)		
Environment	Indoor		
CABLE CONNECTION			
Number of inputs	1		
Number of outputs	1		
Number of taps	8		
Connection Type	QuiCoax		
MECHANICAL			
Product Depth	16 mm		
Product Height	42 mm		
Product Width	159 mm		
Packing QTY	1		
Net Weight	0.177kg		

Ekselans by ITS

Test of: Coupling transfer function (Ed.2)

Information for test

Test Job: 3000 Operator: J.M. Measurement: 05.02.2020 11:47:46
 Test set-up: triaxial cell 1000/150+TELASS 3000 A++
 Remark: triaxial cell 1000/150

Device under test

Item Number: 0000 Cable type: EK RQC 2-1 cell 1000/15
 Type: coaxial Zw: 75.0 Ohm
 Test length: 1.00 m Eps r: 1.5



Test parameter

Start frequency: 10.0 kHz	Gen. Power: 0.0 dBm	Add. parameter of transfer impedance:
Stop frequency: 3.0 GHz	Atten.(P1/P2): 0.0 dB	Test-setup: Short-Matched
Number of points: 801		R1(Z1): 75.0 Ohm
Distance of points: log		R2: 0.0 Ohm Eps r2: 0.0
IF-BW: 10 Hz		Rp: - - - Z2: 0.0 Ohm
Z(NWA): 50.0 Ohm		Rs: - - - lex: 0.0 m

Test diagram

Coupling transfer function (Ed.2) EK RQC 2-1 cell 1000/15

